

Maintainer

- Standard Features –

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / gas spring door holders
- Body primed, undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed LED lights, reflectors, mud flaps and rear body grab handles
- 13.5 Feet of lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval
- 1 Galvannealed rear reel compartment w/ swing-out access doors, rear vapor proof switch panel & open grated deck span in rear step
- 3 Galvannealed underbody storage compartment
- 1 Galvannealed above body storage compartment
- 1 Fold-up deck access ladder on top of bed
- 1 Install charge to mount lube body on chassis

- Chassis Equipment & Accessories -

- 1 Relocate chassis battery
- 1 Electric back up alarm - 97 db at 1 meter
- 1 Add charge to std PTO for Allison auto transmission in lieu of std manual
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Exhaust modify on F650 & F750 chassis to not require body notch
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Four hazard placard decals - ship along

- Hydraulic Equipment & Accessories -

- 1 Closed center LS hydraulic power package, includes PTO, pump, std oil reservoir w/ in-tank filter, vent fill cap, sight gauge
- 1 PTO driveline or adaptor - std. displacement hydraulic pump
- 1 Small oil reservoir (including oil cooler) mounted under Curbside front

- Compressor Equipment & Accessories -

- 1 Quincy 37 displac. CFM hydraulic driven recip. air compressor w/ cover w/ 14 gallon air tank / 24.8 CFM @ 100 PSI / 22.1 CFM @ 150 PSI hydraulic oil cooler built into assembly
- 1 Air accessory package - filter / lubricator / regulator
- 1/2" X 50' spring rewind reel, hose & ball stop

- Lighting / Electrical Equipment & Accessories -

- 6 Exterior 12 v. flood light (halogen)
- 3 Interior 12 v. strip light
- 1 Custom switch panel in rear reel compartment

- Painting Equipment & Accessories -

- 13.5 Feet of unit painted urethane "White" color / Base Charge / List Code: Not a base coat/clear coat or Metallic
- Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on color
- 13.5 Feet of Protective Spray Covering - deck platform & steps, above body compartments and reel compartment top, front & interior

- Roll-out Drawer and Tray Equipment & Accessories -

- 1 Used filter bin mounted in rear reel compartment

- Lube Tanks -

- Tanks equipped with filtered fill caps, suction screen, guarded sight gauge, shut-off valve on tank suction line, tank baffles and tank rack

Maintainer

- Steel Lube Tanks -

1 850 gallon steel tank, DIESEL

- Plastic Lube Tanks and Other Tank Accessories -

3 75 gallon plastic tanks, A/F, 30WT, 90WT

3 135 gallon plastic tanks; HYD, MTR, EVAC

1 "Tank Full" indicator light; EVAC (light mounted on reel)

1 Side panels for plastic tanks

- Hydraulic Driven Pump Kits -

4 Hydra Kit #1 Oil - Commercial-Shearing pump (small displ.)

0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.

0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.

Hannay 1/2" X 50' spring reel & high-flow non-drip rigid dispenser

1 Hydra Kit #4 Anti-Freeze - Hypro pump (non-corrosion resistant)

0-10 GPM delivery

Hannay 1/2" X 50' spring rewind (non-corrosion resistant)

high-flow non-drip rigid dispenser

1 Hydra Kit #5 Oil Evacuation - Commercial-Shearing pump (large displ.)

0-10 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.

0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.

Hannay 1" X 30' spring reel, 4-way control & suction screen

1 Hydra Kit #8 Fuel - Commercial-Shearing pump

20-25 GPM delivery

Hannay 1" X 45' spring rewind reel

1" OPW dispenser & swivel

- Air Driven Pump Kits -

1 Air Kit #12 120# Grease Kit - Graco 50:1 pump (regulator & oiler)

drum cover, follow plate & tie down

Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel

dispenser with swivel

- Lube Equipment & Accessories -

1 Fuel meter 0-30 GPM

1 Fuel filter (30 GPM) maximum flow

1 HP filter 5 micron (hydraulic oils)

2 HP filter 20 micron (mid.wt. oils)

1 HP filter 20 micron (gear oils)

1 Center deck cover for pumps, manifold & plumbing etc

1 Air operated emergency fuel shut-off with fusible link; (one controller in rear compt.)

Options:

1 In-Field Filtration System / large Commercial-Shearing pump / valve

Flow rate - 15-20 GPM / Two 5-micron particle filters / One 10-micron

free-water filter / 3-filter indicator lights / by-pass valve / includes

1 1/4" suction & 1" return both 15' long with threaded ends / no connects

1 In-Field Filtration System / In-line Particle Counter

1 In-Field Filtration System / Data Collection System / req. particle counter

1 Custom above-body compartment with top access door (for filtration system)

1 Additional air controllers for emergency fuel shut-off (2 palm style on front corners)