

Maintainer part number #011025



Selected Options

2008 Ford F-750

Regular Cab XLT (F75)

Vehicle Snapshot

Engine: Caterpillar (7.2L) C7 300 HP @ 2200 RPM. Governed @ 2400 RPM
Transmission: Allison 3000 6-Speed, RDS Series On-Off
Rear Axle Ratio: 4.63
Brakes: Air Brakes - Straight Truck
GVWR: 33,000 lbs

Description	Class
Base Vehicle Price (F75)	STD
Wheelbase	
194" Wheelbase/120" CA/75" AF/308" OAL	OPT
1 - Frame	
Single Channel - Straight 'C' 15.14 SM, 80,000 PSI	STD
<i>High strength low alloy steel: 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.6mm), 437.9 (1122mm) maximum OAL.</i>	
2 - Axle, Front/Suspension, Front	
I-Beam Type - 12,000 lb. Cap. I-120SG	OPT
<i>Steering Wheel - Two Spoke, Black PVC, 17.5" Dia. : Includes Ross TAS-66 power steering gear.</i>	
Taper-Leaf Springs, Parabolic - 12,000 lb. Cap	OPT
<i>Includes shock absorbers.</i>	
3 - Axle, Rear/Suspension, Rear	
21,000 lb. Single-Speed - Spicer 21060S	STD
<i>Single reduction with 190 wheel ends. NOTE: When specifying an axle ratio, check performance guidelines for startability and gradeability.</i>	
Multi-Leaf Springs - Vari-Rate Suspension 23,500 lb. Cap	STD
<i>Includes 4500 lb. auxiliary rubber spring.</i>	
EmGard 75W-90 Synthetic Rear Axle Lube - 1 to 29.99 Pints	OPT

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information. Reference CT05205458 4/25/2007

Selected Options Continued

Description	Class
4.63 Axle Ratio	OPT
4 - Brakes/Brake Equipment	
Air Brakes - Straight Truck <i>Air Compressor, Caterpillar, 16.1 CFM Capacity. Meritor Q-Plus with ABS, Bendix Anti-Lock Brake System, 4-channel. Includes 15" x 4" front brakes, dual direct reading air pressure gauges, front and rear dust shields, brake line color coded nylon, instrument panel mounted yellow knob parking brake control valve, automatic slack adjusters front and rear, two rear spring parking brake chambers, three drain valve(s) and two air tanks (Reference Body Builders Book for location). Rear brake size and components dependent on axle selection.</i>	OPT
Air Dryer, Bendix AD/IP w/Heater, Standard Position <i>Automatic drain valve includes Bendix DV-2 w/heater. Mounted inside left frame rail, back of cab.</i>	OPT
5 - Engine/Engine Equipment	
Caterpillar (7.2L) C7 300 HP @ 2200 RPM, Governed @ 2400 RPM <i>Starting Motor - 12-Volt, 41 MT, Delco-Remy America Inc Type 400 : Less thermal overcrank protection.; Radiator - Modine, 717 Sq In Cross Flow, 4.25 Core w/In-Tank Trans Cooler; Mainshaft Driveline, 1710. 50 State 300 HP @ 2200 RPM, 860 lb-ft Torque @ 1440 RPM, 2400 RPM Governed Speed; 300 Peak HP (Max), with electronic controls. Includes Borg Warner SA85 viscous screw on type fan clutch, Donaldson single stage dry type air cleaner with restriction indicator and Racor non-heated engine mounted fuel/water separator with sight glass. Torque: 860 ft.lbs. @ 1440 rpm.</i>	OPT
Engine Block Heater, Kim Hotstart, 120 Volt/1000 Watt	OPT
Fuel/Water Separator - Racor <i>With electric type heater and sight glass - engine mounted.</i>	OPT
Emissions Surcharge	OPT
6a - Allison Vocational Transmission	
Allison 3000 6-Speed, RDS Series On-Off <i>RDS Series On-Off. Rated: close ratio, 370 HP input power, 1100 lb-ft input torque, 33,000 lbs GVW and 2 year model warranty. PTO provision standard Includes shift key pad.</i>	OPT
Synthetic Transmission Oil, Castrol Transynd - 29 thru 42 Pints	OPT
6b - Allison Programming I/O	
Allison Programming I/O Rugged Duty Series - General Purpose/Construction <i>For programming content specifics, please refer to HELP.</i>	OPT
7 - Exhaust	
Cummins/Caterpillar - Under Cab, Vertical Outlet, Right Side	OPT
Rain Cap, Non-Bright Finish - For Single Vertical Exhaust	OPT

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information. Reference CT05205458 4/25/2007

Selected Options Continued

Description	Class
8 - Electrical/Alternator/Battery	
130 Amp, Leece-Neville 12-Volt, Brush Type, Pad Mounted, Alternator <i>8LHP2170PH.</i>	STD
Two - 625 CCA, 1250 Total, Includes Steel Box and Cover <i>12Volt, Motorcraft, two - 625 CCA, 1250 CCA total, includes steel box and plastic lid.</i>	STD
9 - Fuel Tanks	
Tank - Steel (Deep) 65 U.S. gal. (246 L.) - Single <i>LH D-style steel, top draw, 16" tank depth, mounted left side under cab in front of battery box.</i>	OPT
10 Gal. Single Tank Fuel Fill. Mandatory Charge Applied, Based On Tank Selection	OPT
10 - Seats	
Air Ride Driver, 30%, G-Grain Vinyl w/G-Grain Vinyl Insert <i>Hi-back with integral headrest, dumping/limited reclining, arm rest. Seats are color coordinated to cab trim level. All seats include seat belts.</i>	OPT
2 Passenger, 70% Bench, Folding, G-Grain Vinyl w/G-Grain Vinyl Insert <i>Intermediate folding back, no arm rest, non-suspension. .</i>	OPT
11 - Cab Equipment	
XLT Trim Package <i>(88N) Driver, 40%, Reclining, Mortar Cloth w/Marta Cloth Insert : Hi-back with integral headrest, folding/reclining back, no arm rest, non-suspension. Seats are color coordinated to cab trim level. All seats include seat belts.; (85N) 2 Passenger, 20/40, Folding, Mortar Cloth w/Marta Cloth Insert : Hi-back with integral headrest, folding back, bucket folding outboard, intermediate folding center back creates arm rest with cup holder, non-suspension. Includes molded cloth headliner, RH and LH coat hooks, cloth sunvisors with passenger side mirror, Rigitex back panel trim, molded door trim panels with lower map pocket with carpet on face, soft foamed arm rest, manual Air Conditioning, Power Equipment Group, Radio AM/FM CD, Front Tow Hooks, Bright Front Headlight Bezel, Chrome Grille and Chrome Front Bumper. Flint Gray interior color.</i>	OPT
License Plate Holder, Front <i>Includes upper and lower mounting plate hardware, mounted in existing holes front bumper.</i>	OPT
Mirrors, Dual Stainless Steel - w/Heated & Lighted Heads <i>Rectangular, 7 1/2" x 16 1/2" West Coast style, 102" wide spacing.</i>	OPT
Mirrors, 2 Auxiliary Convex - Stainless Steel <i>8" dia., mounted below primary mirrors.</i>	OPT
Radio AM/FM Stereo - Visteon w/Single CD & Clock <i>Includes four speakers.</i>	STD
12 - Front Wheels/Tires	

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information. Reference CT05205458 4/25/2007

Selected Options Continued

Description	Class
Wheels, Front 22.5x7.5 Painted Steel Disc, 10-Hole <i>(285.75MM BC) hub piloted, flanged nut, metric mount, 7.50 DC rims; with ste hubs, 5 hand hold, white.</i>	STD
Tires, Front Two 11R22.5H Hankook AH12 (503 rev/mile)	STD
13 - Rear Wheels/Tires	
Wheels, Rear 22.5x7.5 Painted Steel Disc, 10-Hole <i>(285.75MM BC) hub piloted, flanged nut, metric mount, 7.50 DC rims; with ste hubs, 5 hand hold, white.</i>	STD
Tires, Rear Four 11R22.5H Hankook DL01 (484 rev/mile)	STD
14 - Miscellaneous	
CPA Fleet Incentive	OPT
Net Invoice Fleet Option	OPT
Interior Colors For : Primary	
Gray	OPT
Primary Colors For : Primary	
Oxford White	OPT
<hr/>	
Vehicle Subtotal	
Destination	
<hr/>	
Vehicle Subtotal (including Destination)	

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information. Reference CT05205458 4/25/2007