

# Maintainer

## - Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Cabinet floor reinforcement w/ clean-out drains
- Three point D-ring door latches w/ gas shock door holders
- Adjustable shelving package
- 49" Wide center deck overlaid with deck plating
- 10" Swing-down tailgate
- 12" Deep, full body width, step bumper w/ 2" square frame hitch receiver rated at Class IV (1,500 lb vert & 10,000 lb MGTW) and 7-prong flat blade (RV style) trailer plug
- Fuel fill recessed into body side rail (1-ton only)
- Body primed, undercoated and includes back-up alarm
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles
- Mini I.C.C. Safety kit - 2 1/2 pound ABC fire extinguisher & hazard reflectors

- 1 MTS-2-084, 59" High X 23" Deep Compartments, 11' Long Body, 12 Ga. body, 54" x 28" wheel well opening / installed on chassis
- 1 Adder for 1 or 2 ton service body "Tall Tower Crane" reinforcement structure of body

NOTE: For individual crane equipment & accessory items ie. adj. boom saddle, outrigger pkgs., body leveling pkgs., hyd. pkgs. to operate a crane or other hyd. drive components - Contact Factory

- 9 Feet of "Standard Compartment" for C-A=154" CT
- 1 SS1, SS2, CS1 & CS2 raised to 70"

## - Hydraulic Cranes (Tall or Short Tower) -

All cranes include a closed center load sensing hydraulic power package consist of a PTO, CC/LS pump, oil reservoir w/ in-tank filter-vented fill cap - sight gauge - suction screen & ball valve, 33 foot remote control w/ proportional trigger & engine start/stop, hydraulic fully extend boom, anti-two block system, overload protection, holding valves, adjustable boom saddle and body spring leveling package (note if air suspension customer will be required to have chassis OEM to provide dual-control)

- 1 Crane 14,000 lb. max. capacity w/ hydraulic extend hex-boom 12' to 24' w/ 2 - rear hydraulic up/down & 1 - hydraulic out crane side out outrigger w/ 2 - front hydraulic up/down & 1 - manual out crane side out outrigger  
Note: Requires 120" C-A minimum (price with per foot body option)
- 1 Install Crane SS Rear

## - Crane Equipment & Accessories -

- 1 Radio-wireless crane remote control, includes: engine start-stop, engine speed control, proportional control and ship along 30' cable for backup

## - Chassis Equipment & Accessories -

- 1 Power-assist shift PTO (Air Shift)
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Fire extinguisher - 20 lbs (ABC)

# Maintainer

## - Hydraulic Equipment & Accessories -

- 1 Hydraulic cooling package, high efficiency bar/plate design, high GPM flow rating - consult factory for usage application
- 1 Hydraulic reservoir tank heater - hot water type
- 1 Large closed center load sensing pump system in lieu of std. CC-LS (req. w/ larger flow & mult operations: large PTO driveline & oil reservoir)
- 1 300 Amp DC hydraulic welder (6,000 watts AC 120/240 volt), Jump Start with side outlets

## - Compressor Equipment & Accessories -

- 1 Model VHP40RMH hydraulic driven recip. air compressor / two-stage w/ 20 gallon air tank / 40 CFM @ 100 PSI / 40 CFM @ 150 PSI includes cover / hydraulic oil cooler build into assembly
- 1 Air accessory package - filter / lubricator / regulator 1/2" X 50' spring rewind reel, hose & ball stop
- 1 Hose reel access out rear compartment

## - Compartment Equipment & Accessories -

- 1 Oxy/Act bottle storage w/ratchet strap, vents, "J" hks. & re/flr.
- 2 2-blowers w/filters for pressurized storage system (PSS) wire to fuse panel with rocker switch
- 1 Front of compartments overlaid w/ aluminum deck plate
- 1 Master compartment locking system, spring loaded and padlock guards
- 4 12-volt electric heaters (1,100 BTU), wire to switch kit in cab

## - Lighting Equipment & Accessories -

- 1 Exterior 12 v. lighting pkg. (halogen) 1-permanent & 1-remote
- 8 Exterior 12 v. flood light (halogen)
- 11 Interior 12 v. strip light
- 1 LED tail, back-up and marker lighting in lieu of std. #007313
- 1 12 volt amber strobe light: CS rear top of body
- 1 Telescopic light pole (2-12 volt flood lights): CS front of body

## - Painting Equipment & Accessories -

- 3 Paint body & tanks complete - one solid urethane color / List color: Black  
Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on colors or metallic.  
Note: For metallic or clear coat/base coat paint additional charges will be required and are not included in this quote unless shown
- 1 Line-X protective spray covering - cargo center deck, compartment tops & sides, front bulkhead, tail gate & extention, bumper and/or workbench area

## - Roll-out Drawer and Tray Equipment & Accessories -

- 1 EZ Latch Aluma (5) drawer std. set (125 lb. cap. Ea.) 18"W x 18"D x (5)-4"H, overall height 29" / 1 F-B divider & 4 S-S adj. Dividers
- 2 EZ Latch Aluma custom drawer HD set (250 lb. cap. Ea.) 29"W x 18" Dx(1)-6", (1)-5" , (5)-4"H overall height 35 w/ 2 F-B divider & 6 S-S adj. Dividers
- 1 Used filter storage cabinet
- 1 HD Riser for grease drum

## - Center Deck Equipment & Accessories -

- 6 Flush mount "D" ring tie-downs in bed floor, each

# Maintainer

- 1 Removable divider panel in center deck to protect tanks
- 1 Step on removable pannel for tank access (Y063)
  
- Rear Bumper Equipment & Accessories -
- 1 26" workbench bumper with 2-side storage compartments includes  
2" square frame hitch receiver and round recessed tail & marker lights
- 1 40,000 lb. Tow rear hitch combo w/ 2" class IV receiver at bottom  
Pintle rated at 6,000 lbs. vert & 40,000 lbs. MGTW  
2" - 3" I.D. with 1 1/4" to 1 5/8" diameter section  
Note: customer is responsible to verify tow rating of chassis and available  
GVWR/GCWR remaining after loading of body and all other items
  
- Miscellaneous Equipment & Accessories -
- 2 Vise / grinder removable mounting plate
- 1 Heavy duty Wilton vise - model 500S
- 1 50' welder lead cables w/ clamp and stinger
- 1 Set of Jumper cable #00 with clamps 30' L
  
- Service / Lube Combo Options
- Tanks equipped with filtered fill caps, suction screen, guarded sight  
gauge, shut-off valve on tank suction line, tank baffles and tank rack
  
- Steel Lube Tanks -
- 2 30 gallon steel tanks: Hyd. & Motor Oil
- 1 500 gallon steel tank : Diesel
  
- Stainless Steel Lube Tanks -
- 1 300 gallon stainless steel tank : Water
  
- Tank Options -
- 1 Sight gauge In-Tank top with indicator in lieu of tank side sight glass
  
- Hydraulic Driven Pump Kits -
- 2 Hydra Kit #1 Oil - Commercial-Shearing pump (small displacement)  
0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.  
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.  
Hannay 1/2" X 50' spring reel & high-flow non-drip rigid dispenser
- 1 Hydra Kit #16 Fuel - Commercial-Shearing pump  
25-30 GPM delivery  
Hannay 1 1/4" X 50' spring rewind reel  
1 1/2" OPW dispenser & swivel
- 1 Hydra Kit #11 High Pressure Washer - Pace 430 pump  
3,000 PSI @ 4 GPM pump output / auto low level shut-off  
Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel  
gun, wand & tip
  
- Air Driven Pump Kits -
- 1 Air Kit #12 120# Grease Kit - Graco 50:1 pump (regulator & oiler)  
drum cover, follow plate & tie down  
Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel  
dispenser with swivel
- 1 Mount Grease CS2 in compartment

# Maintainer

- Lube Equipment & Accessories -

- 1 Air operated emergency fuel shut-off w/ fusible link
- 1 Electric driven rewind reel in lieu of spring: Fuel
- 1 Fuel meter 0-30 GPM
- 1 Fuel filter (30 GPM) maximum flow
- 1 Grease drum hot water heat from chassis, routed down through cover lid